

A25 Antenna

key features

The A25™ GNSS Antenna has been designed to support millimeter accuracy on land and marine applications. The A25 GNSS antenna offers support for present and future GNSS signals, including GPS, GLONASS, BeiDou, and Galileo. A25 is a multi-GNSS precision antenna and is ideal for various applications including surveys, single-frequency RTK positioning and navigation, precise guidance, and machine control. Use the A25 antenna in challenging environments (such as near buildings and foliage) as it has superior multipath mitigation, stable phase center and strong SNR's, even at low elevations. The ruggedized housing utilized by A25 is made of an aluminum base that has been pretreated for the marine environment and will withstand salt, fog, and spray. The antenna easily passes the two-meter pole drop test.



GNSS Antenna

GNSS Sensor

GNSS Reception: GPS L1, GLONASS G1, BeiDou B1, Galileo E1, SBAS, and L-band

GNSS Frequency: 1.525 to 1.615 GHz

LNA Gain: 30 dB

LNA Noise: 2.0 dB, typical

L-Band Sensor

L-Band Frequency: 1.525 - 1.585 GHz

L-Band LNA Gain: 30 dB

Power Input

Input Voltage: 3.3 to 12 VDC

Input Current: 12 mA, typical

Mechanical

Enclosure: Aluminum base with Lexan™ plastic cap

Dimensions: 4.7 H x 15.2 D (cm)
1.8 H x 6.0 D (in)

Weight: .40 kg (.88 lbs)

Mount: 5/8 inch female thread

RF Connector: TNC (straight)

Environmental

Storage Temperature: -40° C to +85° C (-40°F to +185°F)

Operating Temperature: -40° C to +70° C (-40°F to +158°F)

Enclosure Rating: IP69K

Shock and Vibration: EP455

Phase Center Variation: Less than 2 mm at GPS L1, for elevations above 15 degrees



precision@hgns.com
www.hgns.com