

DGPS MAX

Feature-packed sub-meter GPS positioning



DGPS MAX

- Receives GPS, SBAS, OmniSTAR, and beacon signals
- Automatic dual channel SBAS tracking for more reliable reception
- Sub-meter positioning at rates of up to 5 Hz
- Raw measurement data for post-processing applications
- COAST™ technology allows use of corrections for up to 40 minutes without significant performance loss
- Easy configuration using the Setup Wizard
- User-defined profiles save receiver configurations for later use



ESRI
Technology
AUTHORIZED
BUSINESS PARTNER

csi wireless
www.csi-wireless.com

DGPS MAX

Feature-packed sub-meter GPS positioning

GPS Sensor Specifications

Receiver Type:	L1, C/A code, with carrier phase smoothing
Channels:	12-channel, parallel tracking (10-channel when tracking WAAS)
WAAS Tracking:	2-channel, parallel tracking
Update Rate:	1 Hz default, 5 Hz max
Horizontal Accuracy:	<1 m 95% confidence (DGPS*) <5 m 95% confidence** (autonomous, no SA)
Cold Start:	1 min typical
Antenna Input Impedance:	50 Ω

L-band Sensor Specifications

Frequency Range:	1525 to 1559 MHz
Sensitivity:	-120 dBm for $<10^{-3}$ BER
Tuning Mode:	Manual or automatic
Adjacent Channel Rejection:	50 kHz spacing >25 dB, 1 MHz spacing >60 dB

Beacon Sensor Specifications

Channels:	2-channel, parallel tracking
Frequency Range:	283.5 to 325 kHz
Channel Spacing:	500 Hz
MSK Bit Rates:	50, 100, and 200 bps
Operating Modes:	Manual, automatic, semi-automatic
Cold Start Time:	< 1 minute typical
Reacquisition Time:	< 2 seconds typical
Demodulation:	Minimum shift keying (MSK)
Sensitivity:	2.5 μ V/m for 6 dB SNR @ 200 bps
Dynamic Range:	100 dB
Frequency Offset:	± 8 Hz (~ 27 ppm)
Adjacent Channel Rejection:	61 dB ± 1 dB @ $f_o \pm 400$ Hz

Communications

Serial ports:	1 full duplex, 1 RTCM input
Interface Level:	RS-232C
Baud Rates:	4800, 9600, 19200
CAN Bus:	CAN 2.0B
Correction Input / Output Protocol:	RTCM SC-104
Data Input / Output Protocol:	NMEA 0183
Raw Measurement Data:	Proprietary binary (RINEX utility available)
Timing Output:	1 PPS (HCMOS, active high, rising edge sync, 10 k Ω , 10 pF load)
Event Marker Input:	HCMOS, active low, falling edge sync, 10 k Ω , 10 pF load

Environmental

Operating Temperature:	-32°C to +74°C
Storage Temperature:	-40°C to +85°C
Humidity:	95% non-condensing
EMC:	FCC Part 15, Subpart B, Class B CISPR 22

Power

Input Voltage Range:	9.2 to 48VDC
Reverse Polarity Protection:	Yes
Power Consumption:	< 4.8 W
Current Consumption:	< 400 mA @ 12VDC
Load Dump Protection:	Up to 86VDC
Antenna Voltage Output:	5VDC
Antenna Short Circuit Protection:	Yes

Mechanical

Enclosure:	Powder-coated aluminum
Dimensions:	203 mm L x 125 mm W x 51 mm H (8.0" L x 4.9" W x 2.0" H)
Weight:	0.80 kg (1.76 lb)
Display:	2-line x 16-character LCD
Keypad:	3-button
Power Switch:	Push-button
Power Connector:	2-pin miniature
Data Connector:	DB9-socket
Antenna Connector:	TNC-socket

Pin-out

Main Port	
Pin 2	Transmit data (TXD)
Pin 3	Receive data (RXD)
Pin 5	Signal ground

RTCM Input Port

Pin 2	Transmit data (TXD)
Pin 3	Receive data (RXD)
Pin 5	Signal ground
Pin 6	Event marker input
Pin 9	1 PPS

CDA-3 Antenna

GPS Freq. Range:	L1 (1575 MHz ± 20 MHz)
GPS LNA Gain:	27 dB
L-band Freq. Range:	1525 to 1585 MHz
L-band LNA Gain:	28 dB
Beacon Freq. Range:	283.5 to 325 kHz
Beacon LNA Gain:	34 dB

Dimensions:	141 mm dia x 127 mm H (5.57" dia 5.00" H)
Weight:	0.478 kg (1.1 lb)
Antenna Connector:	TNC-socket
Enclosure:	polycarbonate
Mounting Thread:	1-14-UNS-2B
Input Voltage:	5.0 to 15.0VDC
Input Current:	50 to 60 mA

Operating Temp.:	-40°C to +85°C
Storage Temp.:	-40°C to +85°C
Relative Humidity:	100% condensing

* SVs > 5, HDOP < 2, RTCM SC-104 correction data from a dual frequency reference station, short baseline, and low multipath environment.

** Dependent upon ionospheric activity and multipath

© Copyright September 2002, CSI Wireless Inc. All rights reserved. Specifications subject to change without notice. CSI Wireless, the CSI Wireless logo, and COAST™ are trademarks of CSI Wireless Inc. OmniSTAR™ is a registered product and service owned and operated by the Fugro group of companies. Made in Canada. Warranty: Each CSI Wireless product is covered by a limited one-year warranty on parts and labor.

CSIWireless Dealer



Avery label #05260 (laser print)

Printed in Canada.

**csi wireless™**

4110 - 9th Street SE • Calgary • AB • Canada • T2G 3C4
Phone (403) 259-3311 • Fax (403) 259-8866